

# AGLM D011 204w 24144Lm

Reference: FL-OUT-AGLV001

## Description:

High Quality LED Spotlight for outdoor application. Designed to be mounted on 60mm diameter pole. Light Grey Aluminium body and tempered glass diffuser, impact resistant. **Options:**


- Dimming DAI / 1-10V
- Driver with autonomous two-level dimming
- Electric shock protection class II
- RAL colour



## Certifications:



## Fiche technique:

|                       |   |
|-----------------------|---|
| Mounting              | Pole-mounted Ø60mm  |
| Voltage               | 230V  |
| Power                 | 204   |
| Insulation class      | I - (II - OPTION)   |
| Power Factor          | greater than 0.95   |
| Luminous flux         | 24144Lm   |
| Type of light source  | LED   |
| CRI                   | Greater than 80   |
| Driver included       | Yes   |
| Lifetime              | 100 000h L90B10   |
| Color temperature     | 3000K/4000K   |
| Dimming               | OPTION  |
| Angle                 | 5 optics with asymmetric beam   |
| IP                    | 65  |
| IK                    | 08  |
| Operating temperature | -20 ... +40°C   |
| Material              | Polycarbonate   |
| Weight                | 4,90  |
| Size                  | Diameter 500x555mm  |
| Energy label          |  |
| RG                    | RG0   |
| Warranty              | 5 years   |