

120 A

Reference: FL-DL-DRD190-15W

Description:

High quality Recessed Downlight consisting in:

- Aluminium BodyHammered ReflectorDriver and LED included
- 5-year Warranty

Available options:

- Body in Black / Grey / White
 Other Colours/RAL on request
 Power adjusted to application requirement
- Several Beam Angles
- Dimming 1-10V / DALI

Certifications:







Fiche technique:

Voltage 230V 50Hz Power Max. 35w Insulation class I Power Factor Higher than 0.90 Luminous flux Max. 350ULm Type of light source LED Brand of source Philips CRI Higher than 85 Driver included Yes Driver Philips Lefterime 50 000h L80810 Color temperature 3000K/4000K/6000K Dimming Option 1-10V / DALI Angle 60° IP 43 Material Aluminium Weight 0,40kg Diameter de coupe 155mm Size Diameter 174mm Energy label A++		
Power Max. 35w Insulation class I Power Factor Higher than 0.90 Luminous flux Max. 3500Lm Type of light source LED Brand of source Phillips CRI Higher than 85 Driver included Yes Driver Phillips Lifetime 50 000h L80810 Color temperature 3000K/4000K/6000K Dimming Option 1-10V / DALI Angle 60° IP 43 Material Aluminium Weight 0,40Kg Diametre de coupe 155mm Size Diameter 174mm Energy label A++	Mounting	Recessed
Fower Factor	Voltage	230V 50Hz
Power Factor Higher than 0.90 Luminous flux Max. 3500Lm Type of light source LED Brand of source Philips CRI Higher than 85 Driver included Yes Driver Source Philips Color temperature 3000K/4000K/6000K Dimming Option 1-10V / DALI Angle 60° PP 43 Material Aluminium Weight 0,40Kg Diamètre de coupe 155mm Energy label A++ Higher than 9.90 Max. 3500Lm Max.	Power	Max. 35w
Luminous flux Max. 3500Lm Type of light source Erand of source Philips CRI Higher than 85 Driver included Yes Driver Philips Color temperature Dimming Option 1-10V / DALI Angle Material Material Meight O40Kg Diamètre de coupe Energy label Angle Energy label	Insulation class	1
Erand of source Brand of source Philips CRI Higher than 85 Driver included Yes Driver Philips Color temperature Dimming Angle Angle Material Meterial Weight Diamètre de coupe Energy label Park Erergy label Philips Higher than 85 Yes Oxoon L80B10 3000K/4000K/6000K Option 1-10V / DALI 43 Aluminium 0,40Kg Diamètre 174mm A+++ A++ A++ A++ A++ A++ A++	Power Factor	Higher than 0.90
Philips CRI Higher than 85 Driver included Yes Driver Philips Color temperature Dimming Angle Angle Angle Angle Meterial Meterial Meterial Meterial Meterial Energy label Angle Energy label Philips S0 000h L80B10 S0	Luminous flux	Max. 3500Lm
Higher than 85	Type of light source	LED
Priver included Yes Philips Philips Philips Philips Ph	Brand of source	Philips
Driver Philips Lifetime 50 000h L80B10 Color temperature 3000K/4000K/6000K Dimming Option 1-10V / DALI Angle 60° IP 43 Material Aluminium Weight 0,40Kg Diamètre de coupe 155mm Energy label A++ Energy label A++ Energy label 50 000 L80B10 50 000 L80B10 3000K/4000K/6000K Aluminium 0,40Kg Diameter 174mm A++ A++ A++ A++ A++ A++ A++	CRI	Higher than 85
Lifetime 50 000h L80B10 Color temperature 3000K/4000K/6000K Dimming Option 1-10V / DALI Angle 60° IP 43 Material Aluminium Weight 0,40Kg Diamètre de coupe 155mm Energy label A++ Energy label A++ Energy label 50 000h L80B10 3000K/4000K/6000K AHD	Driver included	Yes
Color temperature 3000K/4000K/6000K Dimming Option 1-10V / DALI Angle 60° 43 Material Aluminium Weight Diamètre de coupe 155mm Size Diameter 174mm Energy label A++	Driver	Philips
Dimming Option 1-10V / DALI Angle 60° IP 43 Material Aluminium Weight 0,40Kg Diamètre de coupe 155mm Size Diameter 174mm Energy label A++	Lifetime	50 000h L80B10
Angle 60° Angle 43 Material Aluminium Weight 0,40Kg Diamètre de coupe 155mm Size Diameter 174mm Energy label A++	Color temperature	3000K/4000K/6000K
Material Aluminium Weight 0,40Kg Diamètre de coupe 155mm Size Diameter 174mm Energy label A++	Dimming	Option 1-10V / DALI
Material Aluminium Weight 0,40Kg Diamètre de coupe 155mm Size Diameter 174mm Energy label A++	Angle	60°
Weight 0,40Kg Diamètre de coupe 155mm Size Diameter 174mm Energy label A++	IP	43
Diamètre de coupe 155mm Size Diameter 174mm Energy label A++	Material	Aluminium
Energy label A++ Diameter 174mm A++	Weight	0,40Kg
Energy label A++	Diamètre de coupe	155mm
ATT	Size	Diameter 174mm
Warranty 5 years	Energy label	A++
	Warranty	5 years